

Appl. S.N. 10/633,251  
Amdt. Dated June 20, 2005  
Reply to Office Action of March 21, 2005

124592-1

The listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) A flat panel x-ray tube assembly comprising:

a cathode assembly including a plurality of emitter elements;

an anode substrate having a substrate upper surface facing said plurality of emitter elements and a substrate lower surface, said substrate upper surface positioned parallel to said plurality of emitter elements;

a plurality of target wells formed as at least one line of target wells in said substrate upper surface, each of said plurality of target wells comprising an first angled side surface positioned in an acute angle relative to said substrate upper surface; and

a plurality of first target elements applied one to each of said first angled side surfaces, said first target elements generating x-rays in a direction perpendicular to said plurality of emitter elements in response to electrons received from one of said plurality of emitter elements.

2. (original) A flat panel x-ray tube assembly as in claim 1 further comprising:

a second angled side surface formed in each of said plurality of target wells, each of said second angled side surfaces opposing one of said first angled side surfaces, each of said second angled side surfaces positioned in an acute angle relative to said substrate upper surface; and

a plurality of second target elements applied to each said second side surfaces, said plurality of second target elements generating x-rays in a direction perpendicular to said plurality of emitter elements in response to electrons received from one of said plurality of emitter elements.

3. (original) A flat panel x-ray tube assembly as in claim 1 wherein said first target element comprises a thin film.

4. (original) A flat panel x-ray tube assembly as in claim 1 wherein said first target element comprises tungsten.

5. (original) A flat panel x-ray tube assembly as in claim 1 wherein said first angled surface connects a target well base to said substrate upper surface.

Appl. S.N. 10/633,251  
Amdt. Dated June 20, 2005  
Reply to Office Action of March 21, 2005

124592-1

6. (original) A flat panel x-ray tube assembly as in claim 1 wherein said first target element is in thermal communication with said first angled surface such that thermal energy accruing during the generation of x-rays is dissipated into said anode substrate.

Claim 7. (canceled)

8. (original) A flat panel x-ray tube assembly as in claim 1 wherein said plurality of target wells comprise a two-dimensional matrix of target wells.

9. (currently amended) A flat panel x-ray tube assembly comprising:

a cathode assembly including a plurality of emitter elements, said plurality of emitter elements generating a plurality of electron beams;

a substrate including a plurality of first angled side surfaces, each of said first angled side surfaces in communication with one of said plurality of electron beams, each of said first angled side surfaces angled relative to said plurality of electron beams such that one of said plurality of electron beams approaches one of said first angled side surfaces at an acute angle; and

a plurality of first target elements applied to each of said plurality of first angled side surfaces, wherein said plurality of first target elements comprise at least one line of target elements, each of said plurality of first target elements positioned parallel with one of said plurality of first angled surfaces, each of said plurality of first target elements generating x-rays in a direction parallel to one of said plurality of electron beams.

10. (original) A flat panel x-ray tube assembly as in claim 9 further comprising:

a plurality of second angled side surfaces formed in said substrate, each of said second angled side surfaces facing one of said first angled side surfaces, each of said second angled side surfaces angled relative to said plurality of electron beams such that one of said plurality of electron beams approaches one of said second angled side surfaces at an acute angle; and

a plurality of second target elements applied to each of said plurality of second angled side surfaces, each of said plurality of second target elements positioned parallel with one of said plurality of second angled surfaces, each of said plurality of second target elements generating x-rays in a direction parallel to one of said plurality of electron beams.

11. (original) A flat panel x-ray tube assembly as in claim 9 wherein one of said plurality of electron beams approaches one of said first angled side surfaces at an angle less

Appl. S.N. 10/633,251  
Amdt. Dated June 20, 2005  
Reply to Office Action of March 21, 2005

124592-1

than 45 degrees.

12. (original) A flat panel x-ray tube assembly as in claim 9 wherein said substrate comprises a graphite anode substrate.

13. (original) A flat panel x-ray tube assembly as in claim 9 wherein each of said plurality of first target elements is in thermal communication with said substrate such that thermal energy accruing during the generation of x-rays is dissipated into said substrate.

14. (original) A flat panel x-ray tube assembly as in claim 9 wherein said first target element comprises a thin film.

Claim 15. (canceled)

16. (original) A flat panel x-ray tube assembly as in claim 1 wherein said plurality of first target elements comprise a two-dimensional matrix of target elements.

17. (original) A method of generating a plurality of x-ray beams having a plurality of focal spots comprising:

generating a plurality of electron beams from a plurality of emitter elements;

impacting one of said electron beams into one of a plurality of first target elements, each of said first target elements mounted on a first angled side surface of a substrate;

striking said first target element with said electron beam at an acute angle;

releasing x-rays from each of said first target elements in a direction parallel to one of said plurality of electron beams; and

dissipating thermal energy from each of said plurality of first target elements into said substrate.

18. (original) A method of generating a plurality of x-ray beams having a plurality of focal spots as described in claim 17, further comprising:

impacting one of said electron beams into one of a plurality of second target elements, each of said second target elements mounted on a second angled side surface of said substrate, said second angled side surfaces facing said first angled side surfaces; and

striking said second target element with said electron beam at an acute angle;  
and

releasing x-rays from each of said second target elements in a direction parallel

Appl. S.N. 10/633,251  
Amdt. Dated June 20, 2005  
Reply to Office Action of March 21, 2005

124592-1

to one of said plurality of electron beams.

19. (original) A method of generating a plurality of x-ray beams having a plurality of focal spots as described in claim 17, further comprising:

generating a plurality of x-ray focal spots along a linear line.

20. (original) A method of generating a plurality of x-ray beams having a plurality of focal spots as described in claim 17, further comprising:

generating a plurality of x-ray focal spots along a two dimensional matrix.